

STAR-N and STAR-N PLUS Standard Tile Cutters



STAR-N

New



STANDARD

- 1/2" CUTTING HEIGHT**
- MOBILE SEPARATOR**
- INTERCHANGEABLE SCORING WHEELS**
- DIRECT VISION**
- SHOCK ABSORPTION EFFECT**

ACCESSORIES

- MANUAL DRILL**
- REPETITIVE CUTS**
- 45° CUT**
- MAINTENANCE KIT**



STAR-N PLUS

New



STANDARD

- 12 mm CUTTING HEIGHT**
- MOBILE SEPARATOR**
- INTERCHANGEABLE SCORING WHEELS**
- DIRECT VISION**
- SHOCK ABSORPTION EFFECT**
- REPETITIVE CUTS**
- 45° CUT**

ACCESSORIES

- MANUAL DRILL**
- MAINTENANCE KIT**

STAR-N AND STAR-N PLUS STANDARD TILE CUTTERS

				REF
STAR-40-N - Max. Cutting Length: 17" (42 cm.). With carrying case.	4	48	8413797129915	12991
STAR-50-N - Max. Cutting Length: 21" (51 cm.). With carrying case.	4	48	8413797129939	12993
STAR-40-N - Max. Cutting Length: 17" (42 cm.).	6	72/108*	8413797129908	12990
STAR-50-N - Max. Cutting Length: 21" (51 cm.).	6	72/108*	8413797129922	12992
STAR-40-N PLUS - Max. Cutting Length: 17" (42 cm.). With carrying case.	4	48	8413797129960	12996
STAR-50-N PLUS - Max. Cutting Length: 21" (51 cm.). With carrying case.	4	48	8413797129984	12998
STAR-40-N PLUS - Max. Cutting Length: 17" (42 cm.).	6	72/108*	8413797129953	12995
STAR-50-N PLUS - Max. Cutting Length: 21" (51 cm.).	6	72/108*	8413797129977	12997

STAR-N

- Chromed and rectified steel guides, with anti-corrosion treatment.
- Supplementary base for correct support of the piece.
- With moving Breaking System.
- Includes Scoring Wheel Ø 1/4" (6 mm.) TUNGSTEN CARBIDE.
- Base with shock absorption effect.
- Direct vision of the scoring and cutting line.
- Ø 1/4" (6 mm.) to 13/32" (10 mm.) adaptable and interchangeable scoring wheels.
- Adaptable accessories:
Manual drill (Ref. 15928).
Lateral stop for STAR-N/IN-PLUS (Ref. 12923)
Maintenance Kit (Ref. 18980).

STAR-N PLUS

- Chromed and rectified steel guides, with anti-corrosion treatment.
- Supplementary base for correct support of the piece.
- Support with aluminium guides, maximum rigidity.
- With moving Breaking System and locked sliders for better resistance to bending.
- Includes Scoring Wheel Ø 1/4" (6 mm.) TUNGSTEN CARBIDE.
- With high precision side stop for repeated and 45° cutting
- Base with shock absorption effect.
- Direct vision of the scoring and cutting line.
- Ø 1/4" (6 mm.) to 13/32" (10 mm.) adaptable and interchangeable scoring wheels.
- Adaptable accessories:
Manual drill (Ref. 15928).
Maintenance Kit (Ref. 18980).

	REF					
STAR-40-N	12991	17" (42 cm.)	12x12" (30x30 cm.)	<1/2" (<12 mm.)	•	10.4 Lb (4,7 kg.)
	12990	17" (42 cm.)	12x12" (30x30 cm.)	<1/2" (<12 mm.)	—	8.6 Lb (3,9 kg.)
STAR-50-N	12993	21" (51 cm.)	15x15" (36x36 cm.)	<1/2" (<12 mm.)	•	12.8 Lb. (5,8 kg.)
	12992	21" (51 cm.)	15x15" (36x36 cm.)	<1/2" (<12 mm.)	—	9.7 Lb. (4,4 kg.)
STAR-40-N PLUS	12996	17" (42 cm.)	12x12" (30x30 cm.)	<1/2" (<12 mm.)	•	11.5 Lb. (5,2 kg.)
	12995	17" (42 cm.)	12x12" (30x30 cm.)	<1/2" (<12 mm.)	—	9.5 Lb. (4,3 kg.)
STAR-50-N PLUS	12998	21" (51 cm.)	15x15" (36x36 cm.)	<1/2" (<12 mm.)	•	13.7 Lb. (6,2 kg.)
	12997	21" (51 cm.)	15x15" (36x36 cm.)	<1/2" (<12 mm.)	—	10.6 Lb. (4,8 kg.)