







TS Professional Tile Cutters



Lateral Stop



Chromed and rectified steel guides



Single-point breaker

TS PROFESSIONAL TILE CUTTERS

				REF
TS-30 - Maximum Cutting Length: 14" (36 cm.).	2	32	8413797189308	18930
TS-40 - Maximum Cutting Length: 17" (43 cm.).	2	32	8413797189407	18940
TS-50 - Maximum Cutting Length: 22" (57 cm.).	2	24	8413797189506	18950
TS-50-L - Maximum Cutting Length: 24" (60 cm.).	2	*18	8413797189551	18955
TS-60 - Maximum Cutting Length: 26" (66 cm.).	2	*18	8413797189605	18960

- High Performance Single-point breaker.
- Chromed and rectified steel guides, with anti-corrosion treatment.
- Lateral Stop for straight and 45° Repetitive Cutting.
- Ergonomic Shape and Reinforced Base.
- Supplied with case and complete set of tools (Ø 1/4" (6 mm.) and 13/32" (10 mm.).

- Direct vision of the scoring and cutting line.
- Ø 1/4" (6 mm.) to 7/8" (22 mm.) adaptable and interchangeable scoring wheels.
- Adaptable accessories:
Adjustable Square (Ref. 18820 / 21 / 22).
Manual drill (Ref. 15925 / 27).

REF						
TS-30	18930	14" (36 cm.)	10x10" (25x25 cm.)	1/4-5/8" (6-15 mm.)	881.8 Lb (400 kg)	• 13.2 Lb (6 kg)
TS-40	18940	17" (43 cm.)	12x12" (30x30 cm.)	1/4-5/8" (6-15 mm.)	881.8 Lb (400 kg)	• 14.3 Lb (6.5 kg)
TS-50	18950	22" (57 cm.)	16x16" (40x40 cm.)	1/4-5/8" (6-15 mm.)	881.8 Lb (400 kg)	• 20.5 Lb (9.3 kg)
TS-50-L	18955	24" (60 cm.)	17x17" (42x42 cm.)	1/4-5/8" (6-15 mm.)	881.8 Lb (400 kg)	• 20.9 Lb (9.5 kg)
TS-60	18960	26" (66 cm.)	18x18" (46x46 cm.)	1/4-5/8" (6-15 mm.)	881.8 Lb (400 kg)	• 29.3 Lb (13.3 kg)

